

4" Centerset Gooseneck Faucet

TAG

Architectural/Engineering Specification:

Polished chrome-plated cast brass faucet body with integral shanks, quarter turn ceramic disc cartridges and a 3-1/2" rigid or swing spout. Unit is furnished with a standard 2.2 GPM aerator, vandal-resistant color-coded handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface...

Product Features:

- Ceramic Disc Cartridge
- · Chrome-plated Cast Brass Body
- Widespread Handles Adjustable From 6" to 20" Centers
- 4" Vandal Resistant Color Coded Wrist Blade Handles

Suffix Options:

☐ -FC	2.0 GPM [7.6 L] Laminar Flow Control in
_	Base of Spout
☐ -G	1-1/4" [32mm] Grid Strainer Drain
□ -P	1-1/4" [32mm] Pop-up Drain
-140	Restricted 140° Swing Spout

Compliance and Certification:

- Low-Lead Compliant
- ADA Compliant



*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



Aerator Options:

7.0.u.o. 0,p	Flow rate GPM [LpM]	Vandal Resistant	Pressure Compressation	*WaterSense Labeled	Outlet Type
☐ -2F	2.2[8.3]	✓	✓		Aerator
☐ -3F	0.5[1.9]	✓	✓		Spray
☐ -4F	2.2[8.3]	✓	✓		Laminar
	2.0[7.6]	✓	✓		Aerator
	1.0[3.8]		✓	✓	Spray
	1.0[3.8]	✓	✓		Spray
	1.5[5.7]	✓	✓	✓	Aerator
	1.5[5.7]	✓	✓	✓	Laminar
	1.0[3.8]	✓			Laminar
	0.35[1.3]	✓	✓		Spray
	0.5[1.9]				Laminar
	0.5[1.9]	✓			Laminar
☐ -FC0.5	0.5[1.9]		✓		Plain end
☐ -FC1.0	1.0[3.8]		✓	✓	Plain end
☐ -FC1.5	1.5[5.7]		✓	✓	Plain end
☐ -FC	2.0[7.6]		✓		Plain end

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



4" Centerset Gooseneck Faucet

TAG _____

Rough-in/Overview dimensions

